

# PRODUCT DATASHEET

## HQI-T 70 W/NDL UVS

POWERSTAR HQI®-T G12 | Metal halide lamps with quartz technology for enclosed luminaires



### Areas of application

- Shopping arcades
- Exhibition halls and trade fairs
- Factories and workshops
- Pedestrian zones, public squares
- Buildings, monuments, bridges
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

### Product benefits

- High efficiency
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

### Product features

- POWERSTAR® quartz technology
- Light colors: warm white (WDL), neutral white (NDL)



---

## TECHNICAL DATA


### Electrical data

Nominal wattage	70 W
Construction wattage	74.00 W
Nominal voltage	99 V
Ignition voltage	3.6/5.0 kVp <sup>1)</sup>
Nominal current	0.93 A
PFC capacitor at 50 Hz	12 µF

1) Minimum / Maximum

### Photometrical data

Luminous flux	5400 lm
Luminous efficacy	73 lm/W
Color temperature	4200 K
Color rendering index Ra	80
Light color	842
Rated LLMF at 2,000 h	0.80
Rated LLMF at 4,000 h	0.74
Rated LLMF at 6,000 h	0.68
Rated LLMF at 8,000 h	0.60
UV protection	Yes



### Dimensions & Weight

Overall length	84.00 mm
Light center length (LCL)	56,0 mm
Diameter	25,0 mm
Product weight	30.00 g

### Temperatures & operating conditions

Maximum permitted outer bulb temperature	500 °C
Maximum permitted base edge temperature	280 °C

### Lifespan

Nominal lamp life time	9000 h
Rated lamp survival factor at 2,000 h	0.87
Rated lamp survival factor at 4,000	0.85
Rated lamp survival factor at 6,000	0.80
Rated lamp survival factor at 8,000 h	0.60
Lifespan B50	9000 h

### Additional product data

Base (standard designation)	G12
Mercury content	13.0 mg
Design / version	Clear
System guarantee level	3 (1/5)

### Capabilities

Dimmable	No
Burning position	Any
Enclosed luminaire required	Yes
Hot restart	No

### Certificates & Standards

Energy efficiency class	G
Energy consumption	74.00 kWh/1000h

### Country-specific categorizations

ILCOS	MT/UB-70/842-H/E/SL-G12-25/84
Order reference	HQI-T 70W/NDL U

### Energy labelling regulation data acc EU 2019/2015





Lighting technology used	MH
Non-directional or directional	NDLS
Mains or non-mains	NMLS
Light source cap-type (or other electric interface)	G12
Connected light source (CLS)	No

Color-tuneable light source	No
Envelope	SECOND
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Claim of equivalent power	No
Length	84.00 mm
Height	25,0 mm
Width	25,0 mm
Chromaticity coordinate x	0,372
Chromaticity coordinate y	0,369
Beam angle	SPHERE_360
EPREL ID	666226
Model number	AM42356

## ADDITIONAL PRODUCT INFORMATION

- Burning position: In horizontal burning position of lamp, base pins must be positioned in such a way that they form a horizontal plane.

## DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction High Intensity Discharge Lamp UI
	Certificates EAC RU C-DE.AYA46.B.16087_20 13.10.2020-12.10.2025 Rostest-Moskva - MH single capped
	Certificates EAC N RU D-DE.MU62.B.00932_20 06.03.2020-05.03.2025 Prommash Test - MH
	Declarations of conformity EC Declaration of Conformity - 2021 9C1-4072118-EN-01 - HQI

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321974327	Folding box 1	111 mm x 42 mm x 42 mm	40.00 g	0.20 dm <sup>3</sup>
4008321974334	Shipping box 12	180 mm x 127 mm x 140 mm	567.00 g	3.20 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.