


PRODUCT DATASHEET

HALOLINE 1500 W 230 V R7S

HALOLINE® Standard | Double ended halogen lamps with tube base



Areas of application

- Ideal for emphasizing and accentuating buildings
- General illumination
- Entrance lighting
- Pathway lighting
- Garden lighting
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Outdoor applications only in suitable luminaires

Product benefits

- Brilliant accent light
- No transformer required
- Contains no mercury

Product features

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index R_a : 100
- Color temperature: 3,000 K
- Burning position: p15


TECHNICAL DATA

Electrical data

Nominal wattage	1500.00 W
Construction wattage	1500.00 W
Nominal voltage	230 V
Claimed equiv. conventional lamp power	1500 W
Power factor λ	1.00

Photometrical data

Luminous flux	33000 lm
Luminous efficacy	22 lm/W
Lumen main.fact.at end of nom.life time	0.80
Light color (designation)	Warm White
Color temperature	2900 K
Color rendering index Ra	100
Light color	1029
UV protection	No



Light technical data

Warm-up time (60 %)	0.00 s
Starting time	0.0 s

Dimensions & Weight

Overall length	250.70 mm
Diameter	12 mm
Maximum diameter	12 mm
Product weight	22.92 g

Lifespan

Nominal lamp life time	2000 h
Number of switching cycles	50000

Additional product data

Base (standard designation)	R7s
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Tube
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357 / For outdoor applications and operation in damp locations special approved fixtures are required

Capabilities

Dimmable	Yes
Burning position	p15

Certificates & Standards

Energy efficiency class	C
Energy consumption	1500.00 kWh/1000h

Country-specific categorizations

ILCOS	HDG-1500-230-R7s-256,1
Order reference	64760 1500W 230

Energy labelling regulation data acc EU 2019/2015

Lighting technology used	OTHER
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	R7s
Connected light source (CLS)	No
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Claim of equivalent power	No
Length	256.10 mm
Height	12 mm
Width	12 mm
Chromaticity coordinate x	0.444
Chromaticity coordinate y	0.406
Beam angle	SPHERE_360
EPREL ID	714419
Model number	AC35335

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300004181	Folding box 1	303 mm x 26 mm x 26 mm	31.97 g	0.20 dm ³
4050300209128	Shipping box 12	315 mm x 84 mm x 117 mm	453.52 g	3.10 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.