

PRODUCT DATASHEET

NAV-TS 150 W SUPER 4Y

VIALOX® NAV®-TS SUPER 4Y® | High-pressure sodium vapor lamps for open and enclosed luminaires



Areas of application

- Industrial installations
- Car parks, courtyards
- Buildings, monuments, bridges
- Suitable for use in open and enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- Very high luminous efficacy
- Very good luminous flux maintenance throughout the life of the lamp
- Optimum energy efficiency on POWERTRONIC® PTo 3DIM ECGs

Product features

- Lamp survival factor: 95 % after 16,000 h burning time
- Dimmable on conventional control gears and electronic control gears



TECHNICAL DATA


Electrical data

Nominal wattage	150 W
Construction wattage	150.00 W
Nominal voltage	97 V
Ignition voltage	4.0/5.0 kVp ¹⁾
Nominal current	1.8 A
PFC capacitor at 50 Hz	20 µF

¹⁾ Minimum / Maximum

Photometrical data

Luminous flux	15000 lm
Luminous efficacy	100 lm/W
Color temperature	2000 K
Color rendering index Ra	≤25
Light color	220
Rated LLMF at 2,000 h	0.98
Rated LLMF at 4,000 h	0.95
Rated LLMF at 6,000 h	0.92
Rated LLMF at 8,000 h	0.91
Rated LLMF at 12,000 h	0.89
Rated LLMF at 16,000 h	0.87
Rated LLMF at 20,000 h	0.85
Rated lamp efficacy (standard co.)	100 lm/W
UV protection	No



Dimensions & Weight

Overall length	138.00 mm
Light center length (LCL)	69,0 mm
Diameter	23 mm
Product weight	30.00 g

Temperatures & operating conditions

Maximum permitted outer bulb temperature	650 °C
Maximum permitted pinch temperature	250 °C

Lifespan

Nominal lamp life time	28000 h
Rated lamp survival factor at 2,000 h	0.99
Rated lamp survival factor at 4,000	0.98
Rated lamp survival factor at 6,000	0.98
Rated lamp survival factor at 8,000 h	0.97
Rated lamp survival factor at 12,000 h	0.96
Rated lamp survival factor at 16,000	0.95
Rated lamp survival factor at 20,000 h	0.90
Lifespan B10	20000 h
Lifespan B5	16000 h
Lifespan B50	28000 h
Operation mode LLMF/LSF	50 Hz

Additional product data

Base (standard designation)	RX7s-24
Mercury content	22.0 mg
Design / version	Clear

Capabilities

Dimmable	Yes ¹⁾
Burning position	p45
Enclosed luminaire required	No
Hot restart	Yes

¹⁾ In combination with POWERTRONIC PTo

Certificates & Standards

Energy efficiency class	G
-------------------------	---

Energy consumption	165.00 kWh/1000h
--------------------	------------------


Country-specific categorizations

ILCOS	SD-150-H/E/SL-RX7s24-23/138/H
Order reference	NAV-TS 150W SUP

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	RX7s-24
Length	138.00 mm
Height	23 mm
Width	23 mm

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction High-Intensity-Discharge lamps. Operation instructions

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300281667	Folding box 1	42 mm x 42 mm x 159 mm	52.20 g	0.28 dm ³
4050300281674	Shipping box 12	183 mm x 178 mm x 144 mm	698.00 g	4.69 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.