

PRODUCT DATASHEET

DULUX L 55 W/954 2G11

OSRAM DULUX® L LUMILUX® DE LUXE | CFLni, with 4-pin 2G11 base for ECG/CCG operation, high color rendering



Areas of application

- Offices, public buildings
- Shops
- Supermarkets and department stores
- Hotels, restaurants
- Industry

Product features

- Short and compact pin-base lamp with double-turn tubes
- Single-ended four-pin plug-in 2G11 base
- Very good color rendering index




TECHNICAL DATA

Electrical data


| | |
|----------------------|---------|
| Nominal wattage | 55 W |
| Construction wattage | 55.00 W |
| Nominal voltage | 101 V |
| Nominal current | 0.55 A |


Photometrical data

| | |
|---------------------------|--------------------------|
| Luminous flux | 3600 lm |
| Luminous efficacy | 65 lm/W |
| Light color (designation) | LUMILUX DE LUXE Daylight |
| Color temperature | 5400 K |
| Color rendering index Ra | ≥ 90 |
| Light color | 954 |
| Rated LLMF at 2,000 h | 0.81 |
| Rated LLMF at 4,000 h | 0.77 |
| Rated LLMF at 6,000 h | 0.75 |
| Rated LLMF at 8,000 h | 0.73 |
| Rated LLMF at 12,000 h | 0.71 |
| Rated LLMF at 16,000 h | 0.70 |
| Rated LLMF at 20,000 h | 0.68 |



Dimensions & Weight





| | |
|---|-----------|
| Overall length | 538.00 mm |
| Length with base excl. base pins/connection | 532 mm |
| Diameter | 17,5 mm |
| Tube diameter | 17,5 mm |
| Product weight | 120.5 g |

Temperatures & operating conditions

| | |
|---------------------------|-------------|
| Ambient temperature range | -5...+40 °C |
|---------------------------|-------------|

Lifespan

| | |
|--|---------|
| Nominal lamp life time | 20000 h |
| Service life | 13000 h |
| Rated lamp survival factor at 2,000 h | 0.99 |
| Rated lamp survival factor at 4,000 | 0.99 |
| Rated lamp survival factor at 6,000 | 0.99 |
| Rated lamp survival factor at 8,000 h | 0.99 |
| Rated lamp survival factor at 12,000 h | 0.95 |
| Rated lamp survival factor at 16,000 | 0.81 |
| Rated lamp survival factor at 20,000 h | 0.50 |
| Lifespan B50 | 20000 h |

Additional product data

| | |
|-----------------------------|------------------------|
| Base (standard designation) | 2G11 |
| Mercury content | 5.0 mg |
| Product remark | For ECG operation only |

Capabilities

| | |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

Certificates & Standards

| | |
|-------------------------|---|
| Energy efficiency class | G |
|-------------------------|---|

| | |
|--------------------|-----------------|
| Energy consumption | 58.00 kWh/1000h |
|--------------------|-----------------|

Country-specific categorizations

| | |
|-----------------|-------------------------------|
| ILCOS | FSDH-55/954-/P/-2G11-43,9/533 |
| Order reference | DULUX L 55W/954 |

Energy labelling regulation data acc EU 2019/2015

| | |
|---|--------------|
| Lighting technology used | CFLNI |
| Non-directional or directional | NDLS |
| Mains or non-mains | NMLS |
| Light source cap-type (or other electric interface) | 2G11 |
| Connected light source (CLS) | No |
| Color-tuneable light source | No |
| Envelope | No |
| High luminance light source | No |
| Anti-glare shield | No |
| Correlated colour temperature type | SINGLE_VALUE |
| Claim of equivalent power | No |
| Length | 538.00 mm |
| Height | 17,5 mm |
| Width | 17,5 mm |
| Chromaticity coordinate x | 0,355 |
| Chromaticity coordinate y | 0,350 |
| Beam angle | SPHERE_360 |
| EPREL ID | 546521 |
| Model number | AC34295 |

EQUIPMENT / ACCESSORIES

- Suitable for operation on electronic and conventional control gear

Safety advice

- In case of lamp breakage: www.ledvance.com/brokenlamp

DOWNLOAD DATA

DOWNLOAD DATA



Certificates
EAC RU C-DE.HA46.B.01131_21 21.05.2021-20.05.2026 Expert Certification - CFLpin



Certificates
EAC N RU D-DE.MU62.B.00933_20 06.03.2020-05.03.2025 Prommash Test - CFLpin



Declarations of conformity
EC Declaration of Conformity - 2021 9C1-4077919-EN-00 - DULUX L

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4050300321400 | Folding box 1 | 565 mm x 26 mm x 46 mm | 158.00 g | 0.68 dm ³ |
| 4050300321417 | Shipping box 10 | 572 mm x 136 mm x 109 mm | 1713.00 g | 8.48 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.