

# PRODUCT DATASHEET

## HALOSPOT 111 100 W 12 V 40° G53

HALOSPOT® 111 | Halogen spot lamps with 111 mm aluminum reflector



---

### Areas of application

- General illumination
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings
- Entrance lighting

---

### Product benefits

- Brilliant accent light
- Cap for reduced glare and ease of handling
- Burner with axial filament for optimum distribution of light
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Drastically reduced thermal load in luminaire thanks to aluminum-coated reflector
- Contains no mercury

---

### Product features

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index  $R_a$ : 100
- Diameter: 111 mm


## TECHNICAL DATA

### Electrical data

Nominal wattage	100 W
Construction wattage	100.00 W
Nominal voltage	12 V

### Photometrical data

Luminous intensity	2800 cd
Luminous flux	1200 lm
Nominal useful luminous flux 90°	1200 lm
Luminous efficacy	12 lm/W
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	100
Light color	1030
Rated peak intensity	2800 cd
UV protection	Yes



### Light technical data

Beam angle	40 °
Starting time	0 s
Rated beam angle (half peak value)	40.00 °

### Dimensions & Weight

Overall length	60.00 mm
Diameter	111,0 mm
Product weight	51.67 g

### Lifespan

Nominal lamp life time	4000 h
Number of switching cycles	100000

## Additional product data

Base (standard designation)	G53
Mercury-free	Yes
Design / version	Reflector
Product remark	If connectors are used, an additional holder is required at the rim of the reflector / May produce noise in combination with some dimmers. Recommended solution: use OSRAM HTi DALI 150/230-240 DIM with OSRAM DALI MCU

## Capabilities

Dimmable	Yes
Burning position	Any

## Certificates &amp; Standards

Energy efficiency class	C
Energy consumption	108.00 kWh/1000h



## Country-specific categorizations

ILCOS	HMGS//UB-100-12-G53-111/40
Order reference	41850 WFL ND

## Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G53
Length	67.00 mm
Height	111,0 mm
Width	111,0 mm

## DOWNLOAD DATA

DOWNLOAD DATA	
	CAD data 3-dim 320835_HALOSPOT 111
	CAD data 3-dim 320836_HALOSPOT 111

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300358642	Folding box 1	86 mm x 87 mm x 112 mm	82.67 g	0.84 dm <sup>3</sup>
4050300358659	Shipping box 6	275 mm x 130 mm x 185 mm	625.20 g	6.61 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.