

# PRODUCT DATASHEET SMART+ Filament WiFi Classic A 60 5,5W E27

SMART+ Filament Classic Dimmable | Classic bulb shape with filament-style with WiFi technology



#### Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor applications only in suitable luminaires

#### **Product benefits**

- Wireless control via app
- Easy to install and use
- Contains no mercury

#### **Product features**

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android 4.4 or iOS 9.0)
- Controllable via Google Assistant and Amazon Alexa possible
- RGB color control, approx. 16 million color options adjustable
- Network protocol: WiFi
- Dimmable
- Lifetime: up to 15,000 h
- Light color: Warm White (2,700 K)






## **TECHNICAL DATA**

## Electrical data


Nominal wattage	6 W
Construction wattage	6.00 W
Nominal voltage	220240 V
Nominal current	50 mA
Operating frequency	5060 Hz / 50
Mains frequency	5060 Hz
Power factor λ	> 0.50
Claimed equiv. conventional lamp power	60 W

## Photometrical data

Light color (designation)	Warm White
Lumen main.fact.at end of nom.life time	0.70
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	806 lm
Luminous flux	806 lm
Luminous efficacy	134 lm/W
Color temperature	2700 K
Color rendering index Ra	80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.9








Spectral power distribution

# Light technical data

Beam angle	300 °
Starting time	< 0.5 s

## **Dimensions & Weight**



Product weight	31.00 g
Diameter	60.00 mm
Length	105.00 mm
Width	60.00 mm
Height	60.00 mm
Outer bulb [PICOS]	A60

## Lifespan

Number of switching cycles	100000
Nominal lamp life time	15000 h
Lumen maintenance at end of serv	0.70

## Temperatures & operating conditions

Ambient temperature range	-20+40 °C
5 7 7 7 F 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	

## Additional product data

Mercury-free	Yes	
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value	

Base (standard designation)	E27
-----------------------------	-----

# Capabilities

Dimmable	Yes
Compatible smart home technology	Google Assistant / Amazon Alexa

## Certificates & Standards

Energy efficiency class	E 1)
Energy consumption	6.00 kWh/1000h
Standards	CE
Type of protection	IP20

 $<sup>1) \ {\</sup>sf Energy} \ {\sf efficiency} \ {\sf class} \ ({\sf EEC}) \ {\sf on} \ {\sf a} \ {\sf scale} \ {\sf of} \ {\sf A} \ ({\sf highest} \ {\sf efficiency}) \ {\sf to} \ {\sf G} \ ({\sf lowest} \ {\sf efficiency})$ 

## Energy labellling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	yes
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0.5 W
Networked standby power for CLS	0.50
Claim of equivalent power	Yes
Chromaticity coordinate x	0.463
Chromaticity coordinate y	0.420
R9 Colour rendering index	0.00
Beam angle	SPHERE_360
Survival factor	0.90
Displacement factor	0.50
LED light source replaces a fluorescent light source	not applicable
EPREL ID	644679,644658,644679
Model number	AC32956,AC32941,AC32956

#### **DOWNLOAD DATA**

#### DOWNLOAD DATA



Declarations of conformity

EU Declaration of Conformity - Smart Filament WiFi CL

#### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075528239	Folding box 1	66 mm x 96 mm x 154 mm	116.00 g	0.98 dm <sup>3</sup>
4058075528246	Shipping box 4	210 mm x 165 mm x 145 mm	577.00 g	5.02 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.