Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier: 8711500635273

Type of light source:

| Lighting technology used: | CFLni | Non-directional or directional: | NDLS | | |
|-------------------------------|--------|---------------------------------|------|--|--|
| Light source cap-type | G24D-2 | | | | |
| (or other electric interface) | | | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No | | |
| Colour-tuneable light source: | No | Envelope: | - | | |
| High luminance light source: | No | | | | |
| Anti-glare shield: | No | Dimmable: | No | | |
| Product parameters | | | | | |

| | | Flouuct para | lieter3 | | | |
|--------------------------------------|--|---------------------------|---|-----------------------|--|--|
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| | mption in on- 000 h), rounded est integer | 19 | Energy efficiency class | G | | |
| indicating if it r in a sphere (3 | us flux (фuse), refers to the flux 60º), in a wide in a narrow cone | 1 150 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 6 500 | | |
| On-mode p expressed in W | oower (P _{on}), | 18,3 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | |
| for CLS, expre | ndby power (P _{net}) ssed in W and second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set | 80 | | |
| Outer dimensions without | Height | 150 | Spectral power | See image | | |
| | Width | 27 | distribution in the | in last page | | |
| | Depth | 27 | 1 | Page 1 / 3 | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | | range 250 nm to 800 nm, at full-load | |
|--|---|---|-------|
| Claim of equivalent power ^(a) | - | lf yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,313 |

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

