## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

## **Model identifier:** 8711500623324

## Type of light source:

Lighting technology used:	CFLni	Non-directional or directional:	NDLS		
Light source cap-type	G24Q-1				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					

Parameter   Value   Parameter   Value     General product parameters:     Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer   14   Energy efficiency class   G     Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)   925 in Sphere (360°)   Correlated colour temperature, rounded to the nearest 100 K, that can be set   4 000     On-mode power (Pon), expressed in W   13,8   Standby power (P <sub>sb</sub> ), expressed in W   0,00     Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal   -   Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set   80     Outer dimensions without   Height   130   Spectral power distribution in the in last page   See image distribution in the	General product parameters:   Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer 14 Energy efficiency class G   Useful luminous flux (фuse), ndicating if it refers to the flux n a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) 925 in Sphere (360°) Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set 4 000   On-mode power (P <sub>on</sub> ), expressed in W 13,8 Standby power (P <sub>sb</sub> ), expressed in W 0,00   Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal - Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set 80   Outer Height 130 Spectral power dismensions See image in last page			Product para	meters			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer14Energy efficiency classGUseful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)925 in Sphere (360°)Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set4 000On-mode expressed in W90°)13,8Standby power (Psb), expressed in W and rounded to the second decimal0,00Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set80Outer dimensions WidthHeight130Spectral power distribution in the in last pageSee image in last page	Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer14Energy efficiency classGUseful luminous flux (фuse), n dicating if it refers to the flux n a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)925 in Sphere (360°)Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set4 000On-mode power power (Pon), expressed in W and rounded to the second decimal13,8Standby power (Psb), expressed in W and rounded to the second decimal0,00Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set80Outer dimensions withoutHeight Usith Depth130Spectral power distribution in theSee image in last page	Parameter		Value	Parameter	Value		
mode(KWh/1000 h), rounded up to the nearest integerclassUseful luminousflux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone925 in Sphere (360°)Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set4 000On-mode powerpower (Pon), expressed in W13,8Standby power (Psb), expressed in W and rounded to the second decimal0,00Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set80Outer dimensions withoutHeight130Spectral power distribution in the in last page	mode (kWh/1000 h), rounded up to the nearest integerclassUseful luminous flux (duse), n a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)925 in Sphere (360°)Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set4 000On-mode power (Pon), expressed in W13,8Standby power (Psb), expressed in W and rounded to the second decimal0,00Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set80Outer dimensions withoutHeight130Spectral power distribution in theSee image in last page	General product parameters:						
indicating if it refers to the flux, in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)Sphere (360°)temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be setOn-mode expressed in WPower (Pon), expressed in W13,8Standby power (Psb), expressed in W0,00Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set80Outer dimensions withoutHeight130 27Spectral power distribution in the in last page	Indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)Sphere (360°)temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be setOn-mode power expressed in WPower (Pon), expressed in W13,8Standby power (Psb), expressed in W and rounded to the second decimal0,00Networked standby power (Pnet) for CLS, expressed in W and rounded to the second decimal-Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set80Outer dimensions withoutHeight Udth 27320Spectral power distribution in theSee image in last page	mode (kWh/10	000 h), rounded	14		G		
expressed in W expressed in W and rounded to the second decimal Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal Outer Height 130 Width 27 Pressed in W and rounded to the second decimal Pressed in W and rounded to the	expressed in W expressed in W and rounded to the second decimal Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set Duter dimensions without Height 130 Width 27 Depth 27	indicating if it in a sphere (3 cone (120°) or	refers to the flux 860°), in a wide		temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that	4 000		
for CLS, expressed in W and rounded to the second decimalindex, rounded to the nearest integer, or the range of CRI- values that can be setOuter dimensionsHeight130Spectral distribution in theSee image in last page	for CLS, expressed in W and rounded to the second decimal Duter dimensions without Height 27 Depth 27			13,8	expressed in W and rounded to the	0,00		
dimensions Width 27 distribution in the in last page	dimensions without Depth 27 distribution in the in last page	for CLS, expre	essed in W and	-	index, rounded to the nearest integer, or the range of CRI- values that can be	80		
without Viatin 27	without Depth 27	Outer	Height	130	Spectral power	See image		
without Dopth 27			Width	27	distribution in the	in last page		
	Page	without	Depth	27				

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	- If yes, equivalent power (W)	-
	Chromaticity coordinates (x and y)	0,380

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

