Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier: 8	3711500897435
---------------------	---------------

_	•			
Tyna	Λt	lioht	source	٠.
IVDE	vı	HEILL	JUUILE	- •

Light source cap-type (or other electric interface) Mains or non-mains: CFLNI Non-directional or directional or directional: CYLNI Non-directional or directional or direction or directional or direction or direction or direction	Product parameters			
directional: Light source cap-type GX24Q-3 (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: No Envelope: -	Anti-glare shield:	No	Dimmable:	Yes
directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS):	High luminance light source:	No		
directional: Light source cap-type GX24Q-3 (or other electric interface) Mains or non-mains: NMLS Connected light No	Colour-tuneable light source:	No	Envelope:	-
directional: Light source cap-type GX24Q-3	Mains or non-mains:	NMLS		No
directional:	(or other electric interface)			
	Light source cap-type	GX24Q-3		
Lighting to shool on wood. CFI ni Non directional or NDIC	Lighting technology used:	CFLni	Non-directional or directional:	NDLS

Product parameters

Б .		37.1	1 5	N. 1
Parameter		Value	Parameter	Value
		General product p	arameters:	
	mption in on- 100 h), rounded st integer	32	Energy efficiency class	G
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	2 300 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pexpressed in W	oower (P _{on}),	32,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expre	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	138	Spectral power	See image
dimensions	Width	41	distribution in the	in last page
without	Depth	41	-	
				Page 1 / 3

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	- If yes, equivalent power (W)	-
	Chromaticity coordinates (x and y)	0,380

(a)'-': not applicable; (b)'-': not applicable;

