Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's name | or trade mark: | PHILIPS |
|-----------------|----------------|---------|
|-----------------|----------------|---------|

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| Type | ٥f | liaht | SOLI | rco. |
|------|-----|--------|------|------|
| IVDE | UI. | ווצוונ | SOU | ıce. |

| Lighting technology used: | CFLni | Non-directional or directional: | NDLS |
|-------------------------------|-------|---------------------------------|------|
| Light source cap-type | 2G7 | | |
| (or other electric interface) | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Yes |
| II | | | |

Product parameters

| Parameter | | Value | Parameter | Value |
|-----------------------------------|--|-------------------------|--|--------------|
| | General product parameters: | | | |
| | mption in on- 100 h), rounded st integer | 6 | Energy efficiency class | G |
| indicating if it r in a sphere (3 | us flux (фuse), efers to the flux 60º), in a wide n a narrow cone | 250 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 |
| On-mode prespressed in W | oower (P _{on}), | 5,5 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 |
| for CLS, expres | dby power (P _{net}) ssed in W and second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 82 |
| Outer | Height | 89 | Spectral power | See image |
| dimensions | Width | 28 | distribution in the | in last page |
| without | Depth | 28 | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load | |
|--|---|-------|
| Claim of equivalent power ^(a) | - If yes, equivalent power (W) | - |
| | Chromaticity coordinates (x and y) | 0,463 |

(a)'-': not applicable; (b)'-': not applicable;

