## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark	: PHILIPS
-------------------------------	-----------

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier:	8711500260901
-------------------	---------------

Type of light source:

Lighting technology used:	CFLni	Non-directional or directional:	NDLS
Light source cap-type	2G7		
(or other electric interface)			
N.A.'	NIN AL C	Carrantal Palat	NI -

Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		

High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes

	High luminance light source:	NO		
	Anti-glare shield:	No	Dimmable:	Yes
Product parameters				
	Parameter	Value	Parameter	Value
	General product parameters:			
	Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	9	Energy efficiency class	G
	Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone	600 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of	2 700

indicating if it r in a sphere (3	us flux (φuse), efers to the flux 60º), in a wide n a narrow cone	600 in Sphere (360°)	temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700
On-mode pressed in W	oower (P <sub>on</sub> ),	8,8	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00
for CLS, expres	dby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer	Height	151	Spectral power	See image
dimensions	Width	28	distribution in the	in last page
without	Depth	28		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load	
Claim of equivalent power <sup>(a)</sup>	- If yes, equivalent power (W)	-
	Chromaticity coordinates (x and y)	0,463

(a)'-': not applicable; (b)'-': not applicable;

