Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier's | name o | or trade | mark: | PHILIPS |
|------------|--------|----------|-------|---------|
|------------|--------|----------|-------|---------|

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| Model identifier: | 8711500716385 |
|-------------------|---------------|
|-------------------|---------------|

| Type | of light | source: |
|------|----------|---------|
|------|----------|---------|

| Lighting technology used: | other | Non-directional or directional: | NDLS |
|-------------------------------|-------|---------------------------------|------|
| Light source cap-type | G5 | | |
| (or other electric interface) | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Yes |
| | | | |

Product parameters

| Parameter | | Value | Parameter | Value |
|--------------------------------------|--|-------------------------|--|--------------|
| | | General product p | arameters: | |
| | mption in on- 100 h), rounded st integer | 8 | Energy efficiency class | G |
| indicating if it r in a sphere (3 | us flux (фuse), efers to the flux 60º), in a wide n a narrow cone | 450 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 |
| On-mode pexpressed in W | oower (P _{on}), | 7,1 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 |
| for CLS, expres | dby power (P _{net}) ssed in W and second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 82 |
| Outer | Height | 303 | Spectral power | See image |
| dimensions | Width | 16 | distribution in the i | in last page |
| without | Depth | 16 | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load | |
|--|---|-------|
| Claim of equivalent power ^(a) | - If yes, equivalent power (W) | - |
| | Chromaticity coordinates (x and y) | 0,440 |

(a)'-': not applicable; (b)'-': not applicable;

