Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier:	8711500559678
-------------------	---------------

_	•			
Tyna	Λt	lioht	source	٠.
IVDE	vı	HEILL	JUUILE	- •

Lighting technology used: Other FL Non-directional or directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS): Colour-tuneable light source: No Envelope: Anti-glare shield: No Other FL Non-directional or directional or direction or directional or directional or direction or direction or di	Product parameters			
directional: Light source cap-type G10Q (or other electric interface) Mains or non-mains: NMLS Connected light No source (CLS): Colour-tuneable light source: No Envelope:	Anti-glare shield:	No	Dimmable:	Yes
directional: Light source cap-type (or other electric interface) Mains or non-mains: NMLS Connected light source (CLS):	High luminance light source:	No		
directional: Light source cap-type G10Q (or other electric interface) Mains or non-mains: NMLS Connected light No	Colour-tuneable light source:	No	Envelope:	-
directional: Light source cap-type G10Q	Mains or non-mains:	NMLS		No
directional:	(or other electric interface)			
	Light source cap-type	G10Q		
	Lighting technology used:	other FL		NDLS

Product parameters

Parameter		Value	Parameter	Value
		General product p	arameters:	
	mption in on- 100 h), rounded st integer	33	Energy efficiency class	G
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	2 375 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pexpressed in W	oower (P _{on}),	32,8	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
for CLS, expres	dby power (P _{net}) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	31	Spectral power	See image
dimensions	Width	304	distribution in the in	in last page
without	Depth	304		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	- If yes, equivalent power (W)	-
	Chromaticity coordinates (x and y)	0,440

(a)'-': not applicable; (b)'-': not applicable;

