## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| <b>T</b> | - 6 | 10 - 1 |       |     |
|----------|-----|--------|-------|-----|
| Type     | Λt  | liont  | COLIF | CD. |
| IVDC     | vı  | HEIL   | JUUI  | ·c· |

| Lighting technology used:     | МН   | Non-directional or directional: | NDLS |
|-------------------------------|------|---------------------------------|------|
| Light source cap-type         | G12  |                                 |      |
| (or other electric interface) |      |                                 |      |
| Mains or non-mains:           | NMLS | Connected light source (CLS):   | No   |
| Colour-tuneable light source: | No   | Envelope:                       | No   |
| High luminance light source:  | No   |                                 |      |
| Anti-glare shield:            | No   | Dimmable:                       | No   |
|                               |      |                                 |      |

## **Product parameters**

| Parameter                                                                                             |                                                                            | Value                     | Parameter                                                                                                                                                  | Value        |  |
|-------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--|
| General product parameters:                                                                           |                                                                            |                           |                                                                                                                                                            |              |  |
|                                                                                                       | mption in on-<br>100 h), rounded<br>st integer                             | 40                        | Energy efficiency class                                                                                                                                    | G            |  |
| indicating if it r<br>in a sphere (3                                                                  | us flux (фuse),<br>efers to the flux<br>60º), in a wide<br>n a narrow cone | 3 100 in<br>Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000        |  |
| On-mode pexpressed in W                                                                               | oower (P <sub>on</sub> ),                                                  | 39,1                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal                                                                | 0,00         |  |
| Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal |                                                                            | -                         | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set                                                         | 83           |  |
| Outer                                                                                                 | Height                                                                     | 103                       | Spectral power                                                                                                                                             | See image    |  |
| dimensions                                                                                            | Width                                                                      | 20                        | distribution in the                                                                                                                                        | in last page |  |
| without                                                                                               | Depth                                                                      | 20                        |                                                                                                                                                            |              |  |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800<br>nm, at full-load |       |
|----------------------------------------------------------------------------------------------------|-----------------------------------------|-------|
| Claim of equivalent power <sup>(a)</sup>                                                           | - If yes, equivalent power (W)          | -     |
|                                                                                                    | Chromaticity coordinates (x and y)      | 0,434 |

(a)'-': not applicable; (b)'-': not applicable;

