

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** PHILIPS

**Supplier's address:** Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

**Model identifier:** 8711500203236

## Type of light source:

|   |        |                                 |      |
|---|--------|---------------------------------|------|
| Lighting technology used:                           | HPS    | Non-directional or directional: | NDLS |
| Light source cap-type (or other electric interface) | GX12-1 |                                 |      |
| Mains or non-mains:                                 | NMLS   | Connected light source (CLS):   | No   |
| Colour-tuneable light source:                       | No     | Envelope:                       | No   |
| High luminance light source:                        | No     |                                 |      |
| Anti-glare shield:                                  | No     | Dimmable:                       | No   |

## Product parameters

| Parameter  | Value                  | Parameter  | Value  |
|--|------------------------|--|--|
| <b>General product parameters:</b>   |                        |  |  |
| Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer  | 54                     | Energy efficiency class  | G  |
| Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | 2 400 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 500  |
| On-mode power ( $P_{on}$ ), expressed in W   | 54,0                   | Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal   | 0,00   |
| Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal  | -                      | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set   | 81   |
| Outer dimensions without   | Height                 | 103  | Spectral power distribution in the<br>See image in last page |
|  | Width                  | 20   |  |
|  | Depth                  | 20   |  |

|   |   |                                      |       |
|---|---|--------------------------------------|-------|
| separate control gear, lighting control parts and non-lighting control parts, if any (millimetre) |   | range 250 nm to 800 nm, at full-load |       |
| Claim of equivalent power <sup>(a)</sup>  | - | If yes, equivalent power (W)         | -     |
|   |   | Chromaticity coordinates (x and y)   | 0,478 |

(a) '-': not applicable;

(b) '-': not applicable;

