Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	ALLEGATIES TREGOT	27 (20) 2013/2	ors with regard to energ	By labelling of light
Supplier's name	e or trade mark:	PHILIPS		
Supplier's addr	ess: Customer Ca	are Philips, I.B.R.S./C	.C.R.I. /Numéro 10461,	5600VB Eindhoven, NL
Model identifie	er: 87182912418	81		
Type of light so	urce:			
Lighting techno	logy used:	МН	Non-directional or directional:	DLS
Light source cap-type		E27		
(or other electric interface)				
Mains or non-m	nains:	NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	No
High luminance light source:		No		
Anti-glare shield	d:	No	Dimmable:	No
		Product para	T	
Parameter		Value	Parameter	Value
		General product p	T	I
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		74	Energy efficiency class	G
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		4 500 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode power (P _{on}), expressed in W		73,2	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	92
Outer	Height	123	Spectral power	See image
dimensions	Width	97	distribution in the	in last page
without	Depth	97		

separate control gear, lighting control parts		range 250 nm to 800 nm, at full-load				
and non- lighting						
control parts, if any (millimetre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,434			
Parameters for directional light sources:						
Peak luminous intensity (cd)	14 000	Beam angle in degrees, or the range of beam angles that can be set	30			

(a)'-': not applicable; (b)'-': not applicable;

