Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

| Model identifier: 8 | 8711500181862 |
|---------------------|---------------|
|---------------------|---------------|

| Type | ٥f | liah+ | | |
|------|-----|--------|------|-----|
| Type | OI. | IIKIIL | Soui | ce. |

| Lighting technology used: | HPS | Non-directional or | NDLS |
|-------------------------------|------|--------------------|-----------|
| | | directional: | |
| Light source cap-type | E27 | | |
| (or other electric interface) | | | |
| Mains or non-mains: | NMLS | Connected light | No |
| | | source (CLS): | |
| Colour-tuneable light source: | No | Envelope: | Non-clear |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Yes |
| | | | |

Product parameters

| | | i rodact parai | | |
|-----------------------------------|--|---------------------------|--|--------------|
| Parameter | | Value | Parameter | Value |
| General product parameters: | | | | |
| - · | mption in on- 100 h), rounded est integer | 72 | Energy efficiency class | G |
| indicating if it r in a sphere (3 | us flux (фuse), refers to the flux 60º), in a wide in a narrow cone | 5 600 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 1 900 |
| On-mode pressed in W | oower (P _{on}), | 71,5 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 |
| for CLS, expre | ndby power (P _{net}) ssed in W and second decimal | - | Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set | 125 |
| Outer | Height | 156 | Spectral power | See image |
| dimensions | Width | 71 | distribution in the | in last page |
| without | Depth | 71 | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load | |
|--|---|-------|
| Claim of equivalent power ^(a) | - If yes, equivalent power (W) | - |
| | Chromaticity coordinates (x and y) | 0,540 |

(a)'-': not applicable; (b)'-': not applicable;

