## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

## **Model identifier:** 8711500734037

## Type of light source:

| Lighting technology used:     | HPS    | Non-directional or directional: | NDLS |  |  |
|-------------------------------|--------|---------------------------------|------|--|--|
| Light source cap-type         | PG12-1 |                                 |      |  |  |
| (or other electric interface) |        |                                 |      |  |  |
| Mains or non-mains:           | NMLS   | Connected light source (CLS):   | No   |  |  |
| Colour-tuneable light source: | No     | Envelope:                       | No   |  |  |
| High luminance light source:  | No     |                                 |      |  |  |
| Anti-glare shield:            | No     | Dimmable:                       | No   |  |  |
| Product parameters            |        |                                 |      |  |  |

|  |                                   | i i oddet parai           |   |                       |  |  |
|--|-----------------------------------|---------------------------|---|-----------------------|--|--|
| Parameter  |                                   | Value                     | Parameter   | Value                 |  |  |
| General product parameters:  |                                   |                           |   |                       |  |  |
| Energy consum<br>mode (kWh/100<br>up to the neares                                     | 00 h), rounded                    | 56                        | Energy efficiency<br>class  | G                     |  |  |
| Useful luminou<br>indicating if it re<br>in a sphere (36<br>cone (120º) or in<br>(90º) | efers to the flux 50°), in a wide | 2 500 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 2 500                 |  |  |
| On-mode p<br>expressed in W  | ower (P <sub>on</sub> ),          | 55,5                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00                  |  |  |
| Networked stand<br>for CLS, expres<br>rounded to the s                                 | sed in W and                      | -                         | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 82                    |  |  |
| Outer  | Height                            | 149                       | Spectral power  | See image             |  |  |
| dimensions   | Width                             | 32                        | distribution in the   | in last page          |  |  |
| without  | Depth                             | 32                        | ]   | <br> <br>  Dage 1 / 3 |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) | range 250 nm to 800<br>nm, at full-load |       |
|--|---|-------|
| Claim of equivalent power <sup>(a)</sup>   | - If yes, equivalent power (W)          | -     |
|  | Chromaticity<br>coordinates (x and y)   | 0,478 |

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

