Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: PHILIPS

Supplier's address: Customer Care Philips, I.B.R.S./C.C.R.I. /Numéro 10461, 5600VB Eindhoven, NL

Model identifier: 8727900911534

Type of light source:

| Lighting technology used: | МН | Non-directional or directional: | NDLS | | |
|-------------------------------|------|---------------------------------|------|--|--|
| Light source cap-type | G8.5 | | | | |
| (or other electric interface) | | | | | |
| Mains or non-mains: | NMLS | Connected light source (CLS): | No | | |
| Colour-tuneable light source: | No | Envelope: | No | | |
| High luminance light source: | No | | | | |
| Anti-glare shield: | No | Dimmable: | No | | |
| Product parameters | | | | | |

| | | Product para | lieters | | | |
|--|---------------------|---------------------------|---|--------------|--|--|
| Parameter | | Value | Parameter | Value | | |
| General product parameters: | | | | | | |
| Energy consumption mode (kWh/1000 h), up to the nearest integ | rounded | 74 | Energy efficiency class | F | | |
| Useful luminous flux indicating if it refers to in a sphere (360°), in cone (120°) or in a nar (90°) | the flux a wide | 7 800 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 3 000 | | |
| On-mode power expressed in W | (P _{on}), | 73,2 | Standby power (P _{sb}), expressed in W and rounded to the second decimal | 0,00 | | |
| Networked standby po for CLS, expressed in rounded to the second | W and | - | Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set | 90 | | |
| Outer Heigh | it | 85 | Spectral power | See image | | |
| dimensions Width | | 15 | distribution in the | in last page | | |
| without Depth | า | 15 | | | | |
| 1 • | | 1 | 1 | Page 1/: | | |

| separate control gear, lighting control parts and non- lighting control parts, if any (millimetre) | range 250 nm to 800 nm, at full-load | |
|--|---|-------|
| Claim of equivalent power ^(a) | - If yes, equivalent power (W) | - |
| | Chromaticity coordinates (x and y) | 0,434 |

(a)_{'-'} : not applicable;

(b)'-' : not applicable;

