

Mini-Lynx Fast-Start ML FAST-START 840 E14 8W SLV 0035137



PRODUCT OVERVIEW

Product name	ML FAST-START 840 E14 8W SLV
Technology	Compact Fluorescent
Watt (Rated) (W)	8
Lamp shape	Other
Type	Mini-Lynx Fast-Start
Cap/Base	E14
Lamp finish	Frosted/Coated
General application	Hospitality, Residential & Consumer
ETIM Class	EC000819
E-number FI	4940294
E-number SE	8357534
Luminous flux (lm)	450
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Wattage (W)	8
Average life (Nominal) (h)	12000
Product EAN number	5410288351377
Dimming method	N/A

DATA TABLE

General data

Product name	ML FAST-START 840 E14 8W SLV
Technology	Compact Fluorescent
Watt (Rated) (W)	8

Mini-Lynx Fast-Start

ML FAST-START 840 E14 8W SLV
0035137

Lamp shape	Other
Type	Mini-Lynx Fast-Start
Cap/Base	E14
Lamp finish	Frosted/Coated
General application	Hospitality, Residential & Consumer
ETIM Class	EC000819
E-number FI	4940294
E-number SE	8357534

Optical data

Luminous flux (lm)	450
Luminous flux (Rated) (lm)	450
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	Coo
CRI (Ra)	80
Adjustable chromaticity	N
Lumen maintenance at end of nominal life (%)	75

Electrical data

Wattage (W)	8
Equivalent watt (W)	42
Starting time (max) (s)	<1.5
Warm-up time to 60% of full light (max) (s)	< 40
Current (A)	0.07
Mains voltage (V)	220-240V
Lamp power factor	0.55
Control gear required	No
No. Of switching cycles before premature failures	>50000
Transformer required	No
kWh per 1000 hours burning time	8

Lifetime data

Average life (Nominal) (h)	12000
Average life (Rated) (h)	12000

Physical data

Max. Lamp Diameter (mm) - D	44
Weight (kg)	0.052

Packaging

Single packaging type	Carton
Product EAN number	5410288351377
Packaging single length / height (cm)	12.0
Packaging single width (cm)	4.5
Packaging single depth (cm)	4.5
DUN14 (inner)	25410288351371

Mini-Lynx Fast-Start ML FAST-START 840 E14 8W SLV 0035137

DUN14 (outer)	15410288351374
Units per outer package	10
Packaging outer length / height (cm)	24.0
Packaging outer width (cm)	10.4
Packaging outer depth (cm)	15.0

Safety data

Lamp mercury content (mg)	2.50
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Dry applications use only	kyllä
Suitable for household illumination	kyllä