



318

kWh/1000h

13

lumens/watt

PAR 56

300PAR56/WFL 120V

20849

Product information

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

Application areas



Club and Disco



Product data

Product Code	20849
Bulb Shape	PAR
Bulb Finish	Aluminized
Bulb Diameter [mm]	177.8
Maximum Overall Length [mm]	127
Net weight per piece [g]	648
Gross weight per piece [g]	711
Brand	GE Lighting
Cap/Base	G16d

Performance data

Nominal/ Rated Beam Angle [°]	30
Nominal center beam candlepower (CBCP) [cd]	11000
Rated Lumens [lm]	2600
Weighted energy consumption [kWh/1000h]	318.0
Useful lumens (at 90° cone) [lm]	2600
Energy efficiency class (EEC)	D
Rated Life [h]	2000
Nominal correlated colour temperature (CCT) [K]	2750
Nominal lumens [lm]	3840

Electrical data

Rated power [W]	300.0
Operating Temperature (MAX) [°C]	350
Coil type	CC-13
Ballast Required	Yes
Nominal power [W]	300
Nominal lamp voltage [V]	120

Logistic data

DUN Code	00043168208499
Pack Quantity	12
Layer quantity	96 EUR, 132 UK
Layer quantity EUR	96
Layer quantity UK	132
Pallet quantity EUR (PC)	192
Pallet quantity UK (PC)	264
Outer case size	349 x 300 x 446 (mm)
Product status	Phased-out

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.

