



770
kWh/1000h

71
lumens/watt

Discharge - CSR Turn and Lock (TAL)

CSR700/TAL/PGJX50

76161

Product information

These single-ended metal halide lamps are especially useful for moving-light applications that call for high colour temperatures and brighter light sources. The 'Turn And Lock' technology provides easy installation. A very short arc gap allows for higher beam intensity. This enables good system performance, colour stability and superior lumen maintenance over life. Easy release base (Turn And Lock) enabling quick lamp change at events- High lumen output.

Application areas



Event and Tour



Product data

Product Code	76161
Light Center Length [mm]	65
Bulb Shape	Globe
Bulb Finish	Clear
Bulb Diameter [mm]	18
Maximum Overall Length [mm]	128
Arc Gap	4
Net weight per piece [g]	128
Gross weight per piece [g]	230
Operating position	U - Universal
Brand	GE Lighting
Cap/Base	PGJX50

Performance data

Colour Code	747
Weighted energy consumption [kWh/1000h]	770.0
Energy efficiency class (EEC)	A
Nominal chromaticity coordinate X	0.3
Nominal chromaticity coordinate Y	0.31
Nominal correlated colour temperature (CCT) [K]	7400
Nominal lumens [lm]	50000
Colour Rendering Index (CRI) [Ra]	75

Electrical data

Lamp Current [A]	10
Dimming Capability	Yes
Ballast Required	Yes
Nominal power [W]	700
Nominal lamp voltage [V]	70

Logistic data

DUN Code	10043168761618
EAN Code	0043168761611
Pack Quantity	4
Inner pack type	BOX
Outer pack type	OUTER BOX
Layer quantity	96 EUR, 120 UK
Layer quantity EUR	96
Layer quantity UK	120
Pallet quantity EUR (PC)	480
Pallet quantity UK (PC)	600
Outer case size	175 x 175 x 210 (mm)
Product status	Phased-out

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

Disclaimer

Special Purpose Lamp, Not suited for household illumination

