TUNGSRAM

Innovation is our heritage EST. 1896





Tulox XO Elliptical Diffuse LU100/100/XO/D/E40 TU 93102239

Product information

Tulox XO High Pressure Sodium lamps offer outstanding luminous efficacy, lumen maintenance and long life, thus reducing energy and maintenance costs.

Application areas



Road and tunnel



Street and pedestrian



(**መ**ኸ) Commercial areas



Product data

Product Code	93102239
Bulb Shape	Elliptical
Bulb Finish	Coated
Regulatory comment	ECODESIGN Scope 2019/2020 EU
Bulb maximum overall diameter [mm]	77
Maximum Overall Length [mm]	186
Arc Gap	45.8
Net weight per piece [g]	131
Gross weight per piece [g]	163
Operating position	U - Universal
Mercury Content [mg]	13.3
UV radiance	Exempt
RoHS compliant	Yes
Brand	Tungsram
Cap/Base	E40



Performance data

Weighted energy consumption [kWh/1000h]	102.0
Rated useful lumens [lm]	10200
Rated efficacy [lm/W]	100
Energy efficiency class (EEC)	F
Rated lumen maintenance factor (2000 hours)	0.937
Rated lumen maintenance factor (4000 hours)	0.923
Rated lumen maintenance factor (6000 hours)	0.915
Rated lumen maintenance factor (8000 hours)	0.902
Rated lumen maintenance factor (12000 hours)	0.902
Rated lumen maintenance factor (16000 hours)	0.896
Rated lumen maintenance factor (20000 hours)	0.894
Rated survival factor (2000 hours)	1
Rated survival factor (4000 hours)	1
Rated survival factor (6000 hours)	1
Rated survival factor (12000 hours)	1
Rated survival factor (16000 hours)	0.998
Rated survival factor (20000 hours)	0.991
Nominal chromaticity coordinate X	0.53
Nominal chromaticity coordinate Y	0.43
Nominal correlated colour temperature (CCT) [K]]	2100
Nominal lumens [lm]	10200
Colour Rendering Index (CRI) [Ra]	25




Electrical data

Rated power [W]	102.0	
Lamp Current [A]	1.2	
Run-up time (sec)	<210	
Starting time (sec)	<10	
Hot restart time (sec)	<300	
Dimming Capability	only with specific dimmers	
Ballast Required	Yes	
Nominal lamp voltage range [V]	100	
Morring ramp voltage range [v]	100	
Nominal power [W]	100	
1 0 0		


Logistic data

Shipment	Standard	
DUN Code	15994100017650	
EAN Code	5994100017653	
Pack Quantity	12	
Inner pack type	SLEEVE	
Layer quantity	120 EUR. 168 UK	
Layer quantity EUR	120	
Layer quantity UK	168	
Pallet quantity EUR (PC)	600	
Pallet quantity UK (PC)	840	
Outer case size	331 x 250 x 215 (mm)	
Product status	Available	

Lumen maintenance data



Survival data





Downloads & Links

Go to the catalog site (HTTP)

Product datasheet (PDF)

Datasheet (PDF)

High-res images / Technical drawings (HTTP)

