TUNGSRAM

Innovation is our heritage EST. 1896







Discharge - Single Ended Hot Restrike CSR 6000/SE/HR/UV-C 93106376

Product information

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance

Application areas



Film and Broadcast







Discharge - Single Ended Hot Restrike CSR 6000/SE/HR/UV-C 93106376

Product data

93106376
210
Globe
Clear
85
360
26
1730
1947
U - Universal
Tungsram
G38

Performance data

Colour Code	956
Rated Lumens [lm]	540000
Weighted energy consumption [kWh/1000h]	6600.0
Nominal chromaticity coordinate X	0.333
Nominal chromaticity coordinate Y	0.333
Nominal correlated colour temperature (CCT) [K]]	5600
Nominal lumens [lm]	540000
Colour Rendering Index (CRI) [Ra]	90



Discharge - Single Ended Hot Restrike CSR 6000/SE/HR/UV-C 93106376

Electrical data

Rated power [W]	6000.0
Lamp Current [A]	46
Dimming Capability	No
Ballast Required	Yes
Nominal power [W]	6000
Nominal lamp voltage [V]	130

Logistic data

15994100020728
5994100020721
6
BOX
OUTER BOX
12 EUR, 24 UK
12
24
12
24
760 x 510 x 545 (mm)
Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)



Discharge - Single Ended Hot Restrike

CSR 6000/SE/HR/UV-C 93106376

Disclaimer

Special Purpose Lamp, Not suited for household illumination