TUNGSRAM

Innovation is our heritage EST. 1896







Discharge - Single Ended Hot Restrike CSR200/SE/HR/UV-C 93106379

Product information

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance

Application areas



Film and Broadcast







Discharge - Single Ended Hot Restrike CSR200/SE/HR/UV-C 93106379

Product data

Product Code	93106379
Light Center Length [mm]	38.8
Bulb Shape	Tubular
Bulb Finish	Clear
Bulb Diameter [mm]	19.1
Maximum Overall Length [mm]	80
Net weight per piece [g]	19
Gross weight per piece [g]	200
Operating position	U - Universal
Brand	Tungsram
Cap/Base	GZY9.5

Performance data

Rated Lumens [lm]	17500	
Weighted energy consumption [kWh/1000h]	220.0	
Nominal chromaticity coordinate X	0.333	
Nominal chromaticity coordinate Y	0.3237	
Nominal correlated colour temperature (CCT) [K]] 6000		
Nominal lumens [lm]	17500	
Colour Rendering Index (CRI) [Ra]	90	

Electrical data

Rated power [W]	200.0
Lamp Current [A]	2.9
Dimming Capability	No
Ballast Required	Yes
Nominal power [W]	200
Nominal lamp voltage [V]	70



Discharge - Single Ended Hot Restrike CSR200/SE/HR/UV-C 93106379

Logistic data

15994100020766
5994100020769
10
BOX
OUTER BOX
480 EUR, 600 UK
480
600
5280
5400
195 x 84 x 100 (mm)
Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Disclaimer

Special Purpose Lamp, Not suited for household illumination