## **TUNGSRAM**

Innovation is our heritage EST. 1896







## Discharge - Single Ended Hot Restrike CSR1600/SE/HR/UV-C 93106386

### **Product information**

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance

#### **Application areas**



Film and Broadcast







# Discharge - Single Ended Hot Restrike CSR1600/SE/HR/UV-C 93106386

## Product data

Product Code	93106386
Light Center Length [mm]	85
Bulb Shape	Tubular
Bulb Finish	Clear
Net weight per piece [g]	285
Gross weight per piece [g]	727
Operating position	U - Universal
Brand	Tungsram
Cap/Base	G22

#### Performance data

Rated Lumens [lm]	140000
Weighted energy consumption [kWh/1000h]	1760.0
Nominal chromaticity coordinate X	0.31
Nominal chromaticity coordinate Y	0.31
Nominal correlated colour temperature (CCT) [K]]	6000
Nominal lumens [lm]	140000
Colour Rendering Index (CRI) [Ra]	90

#### Electrical data

Rated power [W]	1600.0
Lamp Current [A]	10.7
Dimming Capability	No
Ballast Required	Yes
Nominal power [W]	1600
Nominal lamp voltage [V]	150



## Discharge - Single Ended Hot Restrike

CSR1600/SE/HR/UV-C 93106386

#### Logistic data

DUN Code	15994100020803
EAN Code	5994100020806
Pack Quantity	6
Inner pack type	BOX
Layer quantity	36 EUR, 66 UK
Layer quantity EUR	36
Layer quantity UK	66
Pallet quantity EUR (PC)	108
Pallet quantity UK (PC)	132
Outer case size	385 x 280 x 346 (mm)
Product status	Available

#### **Downloads & Links**

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

#### Disclaimer

Special Purpose Lamp, Not suited for household illumination