TUNGSRAM

Innovation is our heritage EST. 1896







Discharge - Single Ended Hot Restrike CSR 9000/SE/HR

93106387

Product information

Compact, single ended metal halide hot restrike lamps for a variety of applications requiring high luminance, reliability and excellent colour characteristics. Excellent colour rendering, Ra>90, and high CCT 5600–6000 K with superior colour stability- Universal burn position with hot restrike capability- High efficiency with excellent lumen maintenance

Application areas



Film and Broadcast





Discharge - Single Ended Hot Restrike CSR 9000/SE/HR 93106387

Product data

Product Code	93106387
Light Center Length [mm]	210
Bulb Shape	Tubular
Bulb Finish	Clear
Bulb Diameter [mm]	85
Bulb maximum overall diameter [mm]	85
Nominal Length [mm]	360
Maximum Overall Length [mm]	360
Arc Gap	24
Net weight per piece [g]	880
Gross weight per piece [g]	1700
Operating position	U - Universal
Mercury Content [mg]	650
UV radiance	RG-3
RoHS compliant	Yes
Brand	Tungsram
Cap/Base	G38



Discharge - Single Ended Hot Restrike CSR 9000/SE/HR 93106387

Performance data

958
850000
850000
9900.0
94
250
250
250
250
250
0.323
0.32
] 5800
850000
90

Electrical data

Nominal lamp power factor	0.004
Rated power [W]	9000.0
Ignition Voltage	55
Lamp Current [A]	56
Starting time (sec)	20
Hot restart time (sec)	1
Dimming Capability	No
Ballast Required	Yes
Nominal power [W]	9000
Nominal lamp voltage [V]	160



Discharge - Single Ended Hot Restrike CSR 9000/SE/HR 93106387

Logistic data

DUN Code	15994100020810
EAN Code	5994100020813
Pack Quantity	6
Inner pack type	BOX
Outer pack type	BOX
Layer quantity EUR	12
Layer quantity UK	24
Pallet quantity EUR (PC)	12
Pallet quantity UK (PC)	24
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)

Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Disclaimer

Special Purpose Lamp, Not suited for household illumination