



Single Ended Halogen - HPL

HPL 750-C 115V

93106473

Product information

These lamps encompass modern halogen technology and high production standards. HPL optical system for superior field smoothness and cosine distribution-Integral heat sink base reduces seal temperature, increases durability and maximises life- Shock resistant filament array and patented gas chemistry minimises arc-out risk during alignment and focusing.

Application areas

 Theatre



Product data

Product Code	93106473
Light Center Length [mm]	60.3
Bulb Shape	Tubular
Bulb Diameter [mm]	19
Maximum Overall Length [mm]	106
Net weight per piece [g]	54
Gross weight per piece [g]	73
Brand	Tungsräm
Cap/Base	Special

Performance data

Rated Lumens [lm]	21900
Weighted energy consumption [kWh/1000h]	795.0
Energy efficiency class (EEC)	G
Rated Life [h]	300
Nominal correlated colour temperature (CCT) [K]	3050
Nominal lumens [lm]	21900
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Rated power [W]	750.0
Coil type	4C-8
Ballast Required	Yes
Nominal power [W]	750
Nominal lamp voltage [V]	115

Logistic data

DUN Code	15994100021015
EAN Code	5994100021018
Pack Quantity	12
Layer quantity	468 EUR, 588 UK
Layer quantity EUR	468
Layer quantity UK	588
Pallet quantity EUR (PC)	3276
Pallet quantity UK (PC)	4116
Outer case size	175 x 135 x 138 (mm)
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Entertainment Solution Spectrum Catalogue \(PDF\)](#)

[Lighting design tools & calculators \(HTTP\)](#)

[High-res images / Technical drawings \(HTTP\)](#)

Disclaimer

Special Purpose Lamp, Not suited for household illumination

