TUNGSRAM

Innovation is our heritage EST. 1896





Single Ended Halogen -HPL

HPL 750W 240V 93106508

Product information

These lamps encompass modern halogen technology and high production standards. HPL optical system for superior field smoothness and cosine distribution-Integral heat sink base reduces seal temperature, increases durability and maximises life- Shock resistant filament array and patented gas chemistry minimises arc-out risk during alignment and focusing.

Application areas









Single Ended Halogen - HPL HPL 750W 240V 93106508

Product data

Product Code	93106508
Light Center Length [mm]	60.3
Bulb Shape	Tubular
Bulb Diameter [mm]	19
Maximum Overall Length [mm]	106
Net weight per piece [g]	54
Gross weight per piece [g]	73
Brand	Tungsram
Cap/Base	G9.5

Performance data

Rated Lumens [lm]	18975
Weighted energy consumption [kWh/1000h]	750.0
Energy efficiency class (EEC)	G
Rated Life [h]	300
Nominal correlated colour temperature (CCT) [K]]	3200
Nominal lumens [lm]	18975
Colour Rendering Index (CRI) [Ra]	100

Electrical data

Rated power [W]	750.0
Coil type	6C-8
Ballast Required	No
Nominal power [W]	750
Nominal lamp voltage [V]	240



Single Ended Halogen - HPL HPL 750W 240V 93106508

Logistic data

DUN Code	15994100021350
EAN Code	5994100021353
Pack Quantity	12
Layer quantity	468 EUR, 588 UK
Layer quantity EUR	468
Layer quantity UK	588
Pallet quantity EUR (PC)	3276
Pallet quantity UK (PC)	4116
Outer case size	175 x 135 x 138 (mm)
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)
Entertainment Solution Spectrum Catalogue (PDF)

Lighting design tools & calculators (HTTP)

High-res images / Technical drawings (HTTP)

Disclaimer

Special Purpose Lamp, Not suited for household illumination