# **TUNGSRAM**<sup>™</sup>

Innovation is our heritage EST. 1896






## **Product information**

PAR lamps provide a robust and flexible design solution for a wide range of applications. Choice of PAR36, PAR46, PAR56 or PAR64

- 3000 K or 4200 K colour temperature
- Choice of beam widths
- Excellent colour rendering
- High efficiency combined with low operating costs
- Robust and reliable
- UV control
- Easy retrofit
- Colour consistent throughout life
- Colour blends with halogen and fluorescent

#### Application areas





### Product data

Product Code	93106672
Light Center Length [mm]	80
Bulb Shape	PAR
Bulb Diameter [mm]	204
Maximum Overall Length [mm]	150
Net weight per piece [g]	833
Gross weight per piece [g]	1072
Brand	Tungsram
Cap/Base	GX16d

#### Performance data

Nominal center beam candlepower (CBCP) [cd]15000Rated Lumens [lm]15200Weighted energy consumption [kWh/1000h]1000.0Useful lumens (at 90° cone) [lm]15200Energy efficiency class (EEC)GRated Life [h]300Nominal correlated colour temperature (CCT) [K]]3200Colour Rendering Index (CRI) [Ra]100	Nominal/ Rated Beam Angle [°]	60
Weighted energy consumption [kWh/1000h]1000.0Useful lumens (at 90° cone) [lm]15200Energy efficiency class (EEC)GRated Life [h]300Nominal correlated colour temperature (CCT) [K]]3200	Nominal center beam candlepower (CBCP) [cd]	15000
Useful lumens (at 90° cone) [lm]15200Energy efficiency class (EEC)GRated Life [h]300Nominal correlated colour temperature (CCT) [K]]3200	Rated Lumens [lm]	15200
Energy efficiency class (EEC)GRated Life [h]300Nominal correlated colour temperature (CCT) [K]]3200	Weighted energy consumption [kWh/1000h]	1000.0
Rated Life [h]300Nominal correlated colour temperature (CCT) [K]]3200	Useful lumens (at 90° cone) [lm]	15200
Nominal correlated colour temperature (CCT) [K]] 3200	Energy efficiency class (EEC)	G
	Rated Life [h]	300
Colour Rendering Index (CRI) [Ra] 100	Nominal correlated colour temperature (CCT) [K]] 3200	
	Colour Rendering Index (CRI) [Ra]	100

#### **Electrical data**

Rated power [W]	1000.0
Coil type	C-13
Dimming Capability	Yes
Ballast Required	No
Nominal power [W]	1000
Nominal lamp voltage [V]	240

#### Logistic data

DUN Code	15994100021589
EAN Code	5994100021582
Pack Quantity	6
Layer quantity	24 EUR, 30 UK
Layer quantity EUR	24
Layer quantity UK	30
Pallet quantity EUR (PC)	120
Pallet quantity UK (PC)	150
Outer case size	536 x 391 x 196 (mm)
Product status	Available

Downloads & Links Go to the catalog site (HTTP) Entertainment Solution Spectrum Catalogue (PDF) Lighting design tools & calculators (HTTP) High-res images / Technical drawings (HTTP)

#### Disclaimer

Special purpose lamp – Stage Studio. Not suitable for household illumination.



Tungsram is a registered trademark of Tungsram Operations Kft.

tungsram.com

We in Tungsram Operations Kft. are constantly developing and improving our products. For this reason, all product descriptions in this catalogue are intended as a general guide, and we may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, Tungsram cannot accept any liability arising from the reliance on such data to the extent permitted by law.